

What is claimed is:

1                    1(currently amended).        A shower arrangement, comprising:  
2                    a hollow wall bar running parallel to a wall surface, ~~and configured for~~  
3 ~~fixing a hand shower having~~  
4                    a sliding holder that is movably fixable ~~to~~ along the hollow wall bar  
5 and configured for removably carrying a hand shower,  
6                    wherein the hollow wall bar is connectable at one end of the hollow wall  
7 bar via a water carrying wall connection to a wall water supply, ~~and,~~  
8                    wherein the hollow wall bar ~~comprises at the other end of the hollow~~  
9 ~~wall bar~~ defines a water carrying pipe extending from the wall connection  
10 to at least one shower coupling,  
11                    a shower hose connected to the at least one shower coupling,  
12 ~~such that the shower coupling~~ wherein the hand shower is supplied  
13 with water through the hollow wall bar via the shower hose coupled  
14 between the hand shower and the at least one shower coupling.

1                    2(withdrawn).        The shower arrangement in accordance with claim 1,  
2 further comprising at least one shower supplied with water from the shower  
3 coupling, and a valve device for shut-off of the water between the wall  
4 connection and the shower.

1                    3(withdrawn).        The shower arrangement in accordance with claim 2,  
2 wherein the at least one shower comprises a side shower.

1                    4(withdrawn).        The shower arrangement in accordance with claim 1,  
2 further comprising at least one shower that is fixed to the hollow wall bar and  
3 supplied with water through a radial opening into the wall bar.

1                   5(currently amended).     **A shower arrangement, comprising:**  
2     ~~The shower arrangement in accordance with claim 1, further comprising~~  
3                   **a hollow wall bar connectable at one end of the hollow wall bar via**  
4     **a water carrying wall connection to a wall water supply such that the**  
5     **hollow wall bar is parallel to a wall surface, the hollow wall bar defining a**  
6     **water carrying pipe extending from the wall connection to at least one**  
7     **shower coupling at the other end of the hollow wall bar,**  
8                   **a shower hose coupled to the at least one shower coupling,**  
9                   a hand shower attached via ~~the~~ a shower hose to the shower coupling,  
10                  **a sliding holder that is movable along the hollow wall bar and**  
11     **configured for removably carrying the hand shower,**  
12                  **wherein the hand shower is configured to fit in the sliding holder**  
13     **and to be removable from the sliding holder for adjusting a direction of a**  
14     **shower jet from water carried through the hollow wall bar and the**  
15     **shower hose to the hand shower.**

1                   6(previously presented).     The shower in accordance with claim 1,  
2     further comprising at least one adjustable shower supplied with water through  
3     the hollow wall bar.

1                   7(withdrawn).             The shower arrangement in accordance with claim 1,  
2     further comprising a shower arranged in a housing held on the wall bar.

1                   8(withdrawn).             The shower arrangement in accordance with claim 7,  
2     wherein the housing is movable by at least one of rotation and axial movement  
3     in relation to the wall bar.

1                   9(withdrawn).             The shower arrangement in accordance with claim 8,  
2     wherein the axial movement of the housing in relation to the wall bar is  
3     restricted.

1        10(withdrawn).        The shower arrangement in accordance with claim 7,  
2        wherein a movement of the housing in relation to the wall bar causes a change  
3        in a characteristic of the shower.

1        11(withdrawn).        The shower arrangement in accordance with claim 7,  
2        wherein a movement of the housing in relation to the wall bar is associated  
3        with actuation of a valve device for shut-off of the water between the wall  
4        connection and the shower.

1        12(withdrawn).        The shower arrangement in accordance with claim 7,  
2        wherein the housing supplies at least one additional said shower, whereby the  
3        arrangement comprises plural showers.

1        13(withdrawn).        The shower arrangement in accordance with claim 12,  
2        wherein the plural showers operate simultaneously.

1        14(withdrawn).        The shower arrangement in accordance with claim 12,  
2        wherein the plural showers are operated alternately by a valve device.

1        15(withdrawn).        The shower arrangement in accordance with claims 7,  
2        comprising at least one additional said housing held on the wall bar.

1        16(withdrawn).        The shower arrangement in accordance with claim 15,  
2        wherein the housings are individually adjustable.

1        17(withdrawn).        The shower arrangement in accordance with claim 15,  
2        wherein the housings are adjustable together.

1 18(withdrawn). The shower arrangement in accordance with claim 1,  
2 further comprising a toggle switch between a shower arranged on the wall bar  
3 and a hand shower supplied from the shower coupling.

1 19(withdrawn). The shower arrangement in accordance with claim 7,  
2 wherein the shower is changeable between switch-on/switch-off without  
3 adjustment to the housing.

1 20(withdrawn). The shower arrangement in accordance with claim 7,  
2 wherein a jet direction of the shower can be changed without adjustment to the  
3 housing.

1 21(withdrawn). The shower arrangement in accordance with claim 1,  
2 further comprising at least one shower formed as a side shower.